

AROCS 2640 6X4



CIFA SPA

Mercedes-Benz
Trucks you can trust



Orderdata (Order 1421701247)

A1D	Front axle 8.0 t	L1W	LED turn signals in light signature
A1X	Straight front axle, increased ground clearance	L2H	Side marker lamps, flashing
A2G	Rear axle, crown wheel 300, planetary, 13.4 t	L9A	Pre-installation for rotating beacons
A5W	Axle ratio i = 4.143	L9G	Pre-installation for flood lamp, cab rear wall
B1B	Electronic braking system with ABS and ASR	M0C	Bottom shell to prevent swirling-up of dust
B1F	Heating, electronic air-processing unit	M0Q	Noise regulation acc. to UN-R 51.03, phase 2
B1H	Electr. compressed air supply and control, centre	M2Q	Eng. OM470, inline 6, 10.7 l, 290kW (394hp), 1900 Nm
B1Z	ABS, disengageable	M4X	Engine version Euro VI, E
B2A	Disc brakes on front and rear axle	M5A	2. Engine generation OM470
B2D	Cover plate for brake discs	M5V	High Performance Engine Brake
B2X	Parking brake, electronic	M6L	Air compressor, 2-cylinder
B4A	Condensation monitoring, for compressed air sys.	M7I	Insect screen in front of cooling system
B4M	Air reservoir, steel	M7T	Water pump, governed
B9Y	Deletion, trailer brake and socket	M8A	Air intake from front
C0M	Frame overhang 1350 mm	M9V	Deletion, guard plate, bumper
C1Z	Wheelbase 3900 mm	N2E	PTO MB 131-2c, pump
C5P	Bolted frame	N4Z	Live power take-off, clutch-dependent, MB 1.65
C6C	Steering, single-circuit	N6L	Transmission lock, live power take-off
C6I	Power steering pump, controlled	N6Z	Transmission oil cooling
C6Q	Stabiliser, front axle	N9U	PTO flange with cross serrations, D=120 mm
C6Y	Stabiliser, under frame, rear axle	OWY	Interior measures upgrade
C7K	Battery carrier, batteries stacked	O0A	Coolant service interval, long for non-SWR
C7Q	Free space for crane outrigger feet	O0T	TruckLive
C8F	Wing, for chassis transit	O1T	Interior colour greige/anthracite
C9S	Deletion mounting parts, on frame	O1Z	Steering, indirect
C9Y	Deletion, rear underride guard (ECE)	O2F	PTO, NMV or engine, rear
D0L	Smokers pack	O2N	Starter Melco 95P65
D0S	Compressed-air connection, in cab	O2X	Optimised cab separation point, supply
D1C	Driver's suspension seat, comfort	O3K	Active Safety
D1N	Fold-up co-driver's seat	P0Q	Cover, for wheel arch and engine
D2Y	Seat belt monitor	P0S	Space f. control unit betw. driv.seat & door pocket
D5S	Seat cover, prem. flat-weave fabric, driver's seat	Q1N	Front spring, 8.0 t, 3-leaf
D5T	Seat cover, prem. flat-weave fabr., passenger seat	Q2Q	Rear spring, 2 x 10,0 t, hard
D5Y	Rubber mats, driver's and co-driver's side	Q9Z	Deletion, trailer coupling
D6F	Air conditioning system	R0L	Tyres, customer request, FA
D6I	Residual engine heat utilisation	R0N	Tyres, customer request, RA
D6Z	Construction-site filter	R0O	Tyres, customer request, 2nd RA/twinty.trail.axle
D7G	Stowage compartment lid, driver and co-driver side	R0Z	Wheel-nut cap
D7Q	Stowage facility, high, on engine tunnel	R1Q	15-degree tapered rims, 9.00 x 22.5
D8A	Roof hatch/vent, roof	S1H	Lane Keeping Assist
E0D	Battery sensor, Hella	S1L	Attention Assist
E0F	Batteries from company Exide	S1O	Traffic Sign Assist
E1B	Batteries 2 x 12 V/170 Ah, low-maintenance	S1Y	Tyre pressure monitor
E1N	Alternator 28 V/100 A	S2D	Active Brake Assist 6
E3L	Socket, 24 V/15 A, co-driver footwell	S2H	Active Sideguard Assist 2

Orderdata (Order 1421701247)

E3W	PSM, 2nd generation	S2L	Frontguard Assist
E4C	Additional functions, for body manufacturer	S4A	Pre-installation for alcohol test on start-up lock
E5A	No. 1 switch, for non-MB body electrics	S5A	Speed limiter, 90 km/h (56 mph), ECE
E5B	No. 2 switch, for non-MB body electrics	S5Z	Cruise control
E5C	No. 3 switch, for non-MB body electrics	S8A	First aid kit
E5H	Switch for night-time driving light	S8C	Hazard warning triangle
E6Y	Reverse warning, comb. with hazard warning lights	S8D	Warning lamp
F0E	M-cab, low roof, 2.30 m, tunnel 320 mm	S8E	Reflective safety jacket
F0G	Side module, N3G vehicle	S8H	Fire extinguisher, 6 kg
F0Y	Mirror cover, construction vehicle	U0Q	Control code, HDEP Fuel Efficiency Package - FE1
F1Q	M-cab	U1W	AdBlue lines, water-heated
F2C	Floor variant, tunnel 320 mm	U2G	Exhaust box
F2G	Cab width 2.30 m	U2M	Control code, ASAM
F2M	Cab, 420 mm attachment height	U2T	Control code, exhaust box, rear outlet
F2Y	ClassicSpace Low Roof	U2U	Control code, catalytic converter kit 1
F3B	Cab mountings, comfort, steel-sprung	U3D	Control code, CAN star points, classic
F3W	Cab tilting mechanism, mechanical-hydraulic	U3F	Control code, global AdBlue sensor (GMS DEF)
F4H	Cab rear wall, without window	U3N	Control code, navigation map, EU region
F4X	Stowage compartment exterior flap, left	U3S	3rd-generation electronics architecture
F5L	Sun visor, exterior, transparent	V0Q	Vehicle version in acc. w. GSR, phase B
F5Y	A-pillar trim	V0T	Vehicle class N3G, off-road vehicle
F6D	Windscreen, tinted, with filter band	V0U	Overhang angle, front, minimum 25 degrees
F6I	Front mirror, heated	V0W	Breakover angle, minimum 25 degrees
F6Q	Air horn	V0X	Ground clearance under front axle, minimum 250 mm
F7B	Bumper, with steel corners	V0Y	Ground clearance under rear axle, minimum 250 mm
F7D	Bumper centre section w. towing eyes, coupling	V0Z jaw	Ground clearance between axles, minimum 300 mm
F7Y	Cab entrance, left/right, movable	V1B	Arocs
F8B	2 remote control keys	V1W	Standard
F8E	Locking system, with central locking	V2J	Arocs model generation 5
F8F	Extended central locking	V7M	Body type: concrete pump
F8H	2 remote control keys, additional	V8A	Chassis number FIN
F8V	Light sensor	V9G	Technical changes model year October
F8W	Rain sensor	W4E	Weight variant 28.0 t (8.0/10.0/10.0)
G0K	Drive program, economy/power	X2E	Model plate, EU
G0R	Transmission support arms, optimised for removal	X2T	Maintenance Documentation
G0T	Predictive Powertrain Control	X2Y	Registration certificate, Part II, prepared
G2D	Transmission G 280-16/11.7-0.69	X3O	Mercedes-Benz OnRoadService
G5B	Double-disc clutch	X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
G5G	Mercedes PowerShift 3	X4S	ATS warranty according to GTC, 4th year/340,000 km
G5L	PowerShift Advanced	Y1F	Assignment of cab paintwork, top coat line 1
G5Y	Tachograph calibration, digital, ex factory	Y4J	2 wheel chocks
I2G	Tyres tubeless, 315/80 R 22.5, fr./lead./trl. axle	Y4Y	Tyre inflating hose

Orderdata (Order 1421701247)

I2H	Tyres, tubeless, size 315/80 R 22.5, rear axle	Y4Z	Compressed-air gun, with hose
I4I	Wheel arrangement 6x4	Y9X	Deletion, bracket, wheel chock
I5F	26.0-tonner	Z1H	EBS, Wabco
I6A	Rigid chassis	Z1Y	EAPU equipment, item 2
I6I	Vehicle production plant Wörth	Z3A	Switch module 1, type A
I6K	Heavy-duty model series, new generation from 18 t	Z3D	Switch module 2, type B
I6M	Heavy-duty vehicles from 18 t, off-road	Z3F	Switch module 7
I6W	Leaf suspension, rear axle	Z3H	Side marker lights, 1st pair
J0U	Remote update of driving assistance map	Z3J	Side marker lights, 3rd pair
J1M	Dig. tachograph, 2nd gen., version 2, ADR	Z3K	Side marker lights, 4th pair
J1S	Tachograph manufacturer VDO	Z4B	Domestic (Germany)
J2K	Speaker, 2-way system	Z4O	Tank cross-section, narrow
J2U	Navigation system	Z4Q	Tank cross-section, low
J6C	Multimedia Cockpit, interactive	Z5D	OM 470
J6W	Reversing camera, towing vehicle end	Z5G	Fan position, on crankshaft
J7A	Truck Data Center 8	Z5I	Fan ratio, 1:1.0
J7V	Driving assistance map, Europe region	Z5M	PTO, single
J8U	Pre-installation for Truck Data Center 8	Z5P	Clutch supplier F&S
J9D	Provision for fitting toll tracking	Z5S	Power take-off, pump, under top edge of frame
K0T	Main tank, left	Z5V	Starter with M10, HDEP
K1C	Tank, 290 l, left, 650 x 565 x 950 mm, aluminium	Z5X	Left-hand drive
K3V	AdBlue tank, 60 l, left	Z5Y	Vehicle, for right-side traffic
K5M	Tanks, lockable	Z7J	Aluminium battery lines
K5Q	Fuel screen, tank filler neck	Z8E	Plausibility control code (internal)
K5S	Protective cap for AdBlue metering system	Z8P	CTT vehicle, conversion on assembly line
K8D	Exhaust sys.,tailpipe to right/outwards,horizontal	Z8U	CTT vehicle
L0A	Illumination regulation, in acc. with UN-R 48.06	Z9A	Constructability request order, special control
L1C	LED daytime running lamps		

SP-REQ. no.	Description
W/JC7K	Battery carrier, batteries stacked
W/JC7Q	Free space for crane outrigger feet
W/JZCD	"Cifa" customer vehicle